

Data Sheet

FUJITSU PLAN EP E810-CQDA2 2X 100G QSFP28

Dual-port 100 Gbit PCIe 4.0

Ethernet cards enable data exchange between all the devices connected in a local network (LAN). A networked IT infrastructure that functions well is of great significance when managing and controlling critical business processes in a company. The wide range of complex information transported across the network relies on fast and reliable data processing by the network cards.

PLAN EP E810-CQDA2 2X 100G QSFP28

The FUJITSU PLAN EP E810-CQDA2 2X 100G QSFP28 Server Adapter is the most flexible and scalable Ethernet adapter for the current demanding data center environments from Intel.

This adapter family addresses the demanding needs of today's generation agile data center by providing unmatched features for both server and network virtualization, flexibility for LAN networks and proven, reliable performance. The PLAN EP E810-CQDA2 2X 100G QSFP28 adapter delivers superior performance in a PCI Express 4.0 slot.



Features & Benefits

Main Features	Benefits
<p>Scalable performance</p> <ul style="list-style-type: none">■ Intel® E810-CQDA2 QSFP28 Dual-Port 100GbE Network Adapter	<ul style="list-style-type: none">■ Cost- and energy-efficient design delivers superior performance with a theoretical throughput of 100 Gb/s (50 Gb/s Tx; 50Gb/s Rx) bidirectional throughput
<p>Flexible technology options</p> <ul style="list-style-type: none">■ Server Virtualization and VMDq	<ul style="list-style-type: none">■ The host-based virtualization technologies supported by Intel VT include VMDq for Emulated Path: Adapter-based Queue sorting enabling efficient hypervisor-based switching
<p>Efficient networking</p> <ul style="list-style-type: none">■ A Complete, Unified Networking Solution	<ul style="list-style-type: none">■ Converging data and storage onto one fabric eliminates the need for multiple adapters, cables and switches
<p>Connectivity</p> <ul style="list-style-type: none">■ SR-IOV for Direct Assignment	<ul style="list-style-type: none">■ Adapter-based isolation and switching for various virtual station instances enabling optimal CPU usage in virtualized environments

Technical details

Technical details

Controller Silicon	Intel® Ethernet Controller E810-CAM2
Controller type	Ethernet Ctrl.
Connector type	QSFP28
Released drivers list link	http://support.ts.fujitsu.com/Download/Index.asp
Number of ports	2
Number of Connectors	2
Number of external ports	2
Data transfer rate(s)	100 Gbit/s
Auto Negotiation support	Yes
Bus interface	PCIe 4.0 x16
Bus type	PCIe 4.0
Bus transfer rate	16GT/s
LEDs	ACTIVITY (blinking) NO ACTIVITY (off) LINK SPEED (green = 100GbE; amber = less than 100GbE; off = no link)
Interrupt Levels	MSI-X
WoL	No
Virtualization	<ul style="list-style-type: none"> - Host virtualization via VMDQ and SR-IOV - Up to 256 SR-IOV Virtual Functions - Stateless offloads for tunneled packets (network virtualization support) - Malicious VF protection - Virtual machine load balancing (VMLB) - Advanced packet filtering - VLAN support with VLAN tag insertion, stripping and packet filtering for up to 4096 VLAN tags - VxLAN, GENEVE, NVGRE, MPLS, VxLAN-GPE with Network Service Headers (NSH) - Intel® Ethernet Adaptive Virtual Function drivers

Teaming	Depends on OS
Remote boot support	PXE
Offloading	<ul style="list-style-type: none"> - TCP Stateless Offloads (include checksum, TSO, VMDq and RSS) - TX/RX IP, SCTP, TCP & UDP checksum offload (IPv4, IPv6) capabilities - iSCSI Host Initiator - Flow Classification (Trafficking data flows across multiple consumers and connections)

Data transfer rate up to	100 Gbit/s
--------------------------	------------

Order code	Product Name	Height of bracket	Number of ports	Related product
PYBLA432L	PLAN EP E810-CQDA2 2X 100G QSFP28 PCIe LP	Low Profile (LP)	2	PRIMERGY Server
PYBLA432	PLAN EP E810-CQDA2 2X 100G QSFP28 PCIe	Full Height (FH)	2	PRIMERGY Server
PY-LA432	PLAN EP E810-CQDA2 2X 100G QSFP28 PCIe	Full Height / Low Profile	2	PRIMERGY Server

Supported Interface Modules / Cables

Order code	Application	Type / mode	Connector / cable Length
PYBSFPS54	Ethernet 100 Gbit/s	QSFP28 / MMF (SWL)	up to 100m
PY-SFPS54	Ethernet 100 Gbit/s	QSFP28 / MMF (SWL)	up to 100m

Environment

Power consumption	typ. 20.8 W, max. 13.7 W
Temperature (operating)	0 - 60 °C
Storage temperature	-40 - 70 °C

Compliance

Compliance notes	According to the corresponding system
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

More information

Fujitsu products, solutions & services

In addition to Fujitsu with PLAN EP E810-CQDA2 2X 100G QSFP28, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PLAN EP E810-CQDA2 2X 100G QSFP28, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/primergy>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>
Copyright 2023 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Limited
Website: www.fujitsu.com/primergy
2023-06-02 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>
Copyright 2023 FUJITSU LIMITED