



eW Downlight Powercore

BCS401 9xLED-4000 65 100-277V

9 pcs - LED High Brightness - Beam angle 65° - Polycarbonate bowl/cover - 65°

eW Downlight Powercore is a low-profile, surface-mounted LED downlight for basic white general illumination. This easy-to-install, dimmable downlight is ideally suited to lobbies, corridors, elevators, conference rooms, common spaces, kitchenettes, and interiors in commercial, hospitality, retail, and residential environments. With its unobtrusive, sleek design, eW Downlight Powercore is especially appropriate where recessed installation is not possible. Integrated Powercore technology ensures rapid, efficient and accurate control of power output to the fixture directly from line voltage, eliminating the need for remote transformers or other external power supplies. Use of standard wiring dramatically simplifies installation and helps lower total system cost.

Product data

General Information		CE mark	CE mark
Number of light sources	9 [9 pcs]	CCC mark	CCC mark
Lamp family code	LED-HB [LED High Brightness]	FCC mark	FCC Class B
Light source colour	Neutral white	Operating and Electrical	
Light source replaceable	No	Input frequency	50 to 60 Hz
Optic type	65 [Beam angle 65°]	Control signal voltage	1-10 V DC
Optical cover/lens type	PC [Polycarbonate bowl/cover]	Mechanical and Housing	
Luminaire light beam spread	65°	Housing material	Aluminum die-cast
Ready-to-install	Ready-to-install	Optic material	Polycarbonate
Flammability mark	F [For mounting on normally flammable surfaces]		

eW Downlight Powercore

Optical cover/lens material	Polycarbonate
-----------------------------	---------------

Approval and Application

Ingress protection code	IP20 [Finger-protected]
-------------------------	--------------------------

Initial Performance (IEC Compliant)

Initial luminous flux	902 lm
Initial luminous flux at color temperature of 4000 K	902 lm
Initial LED luminaire efficacy	64.9 lm/W
Initial input power	15 W

Over Time Performance (IEC Compliant)

Lumen Maintenance 70% at 25°C Reported	60000
--	-------

Application Conditions

Ambient temperature range	-20 to +50 °C
---------------------------	---------------


Maximum dimming level	20% (depends on dimmer, ELV)
Suitable for random switching	Yes (relates to presence/ movement detection and daylight harvesting)

Product Data

Full product code	871829138066599
Order product name	BCS401 9xLED-4000 65 100-277V
EAN/UPC – product	8718291380665
Order code	38066599
Numerator – quantity per pack	1
Numerator – packs per outer box	6
Material no. (12NC)	910503702743
Net weight (piece)	0.720 kg



Dimensional drawing



eW Downlight Powercore gen2

