

# Data Sheet FUJITSU Storage ETERNUS DX100 S5 Disk System

The all-in-one storage system for SMBs or subsidiaries



#### ETERNUS DX - Business-centric Storage

FUJITSU Storage ETERNUS DX series are the ideal hybrid storage for on-premise storage of business-critical data in data centers, branch offices and self-operated IT of SMBs, something every business can afford, with integrated and powerful features for business growth, efficiency and continuity. Latest capacity and performance optimization capabilities contribute to overall business efficiency, outstanding data-safe technologies and all-inclusive encryption guarantee uncompromised business continuity.

#### **ETERNUS DX100 S5**

The scalable and unified Fujitsu Storage ETERNUS DX100 S5 delivers enterprise-class functionality to small and medium-sized companies and subsidiaries with an excellent price/performance ratio. It is the perfect solution when consolidating data for server virtualization, e-mail, databases and business applications as well as centralized file services. Simple, intuitive system management, highly flexible connectivity, granular scalability and the option to upgrade to a higher system significantly reduce operational and migration costs. The ETERNUS DX family architecture lets customers benefit from software options such as - thin provisioning, automatic storage tiering, transparent failover and quality of service management even in the entry-level class. All of which contribute to better business support and quarantees continuity and efficiency in daily operations



Page 1 / 6 www.fujitsu.com/eternus

### Features & Benefits

| Main Features                         | Benefits  |
|---------------------------------------|---|
| Maximum utilization and consolidation |   |
|                                       | Massive scalability makes it perfect for any future requirements.<br>Flexible combination of flash and disk media allow a broader scope<br>of deployments, while unified SAN and NAS access drives system<br>utilization and enhances ROI. Outstanding benchmark results with<br>ultra-low latency and all-inclusive free-of-charge management suite<br>ETERNUS SF Express make it the ideal RAID system. |
| Round-the-clock Business Continuity   | ETERMOS SI EXPICES Make it the local IV ilo system.   |
| ,                                     | Avoid planned or unplanned downtimes with replication and<br>Storage Cluster. Transparent failover allows 100% data insurance<br>and non-stop operations, as well as a system availability of<br>99.9999%. Intelligent snapshot functionality supports secure<br>backups.   |
| Automated Quality-of-Service          | <ul> <li>Control application priorities according to business needs, minimize<br/>admin efforts, automate monitoring and adjustment to guarantee<br/>service levels</li> </ul>  |

Page 2 / 6 www.fujitsu.com/eternus

## Technical details

|   | 2.5-inch Controller Enclosure   | 3.5-inch Controller Enclosure   |  |  |  |  |  |
|---|---|---|--|--|--|--|--|
| No. of controllers                        |   | 1/2   |  |  |  |  |  |
| No. of host interfaces                    | 4/8 ports [FC(32Gbit/s,16Gbit/s), iSCSI(10Gbit/s,1Gbit/s), SAS(12Gbit/s), Ethernet(10Gbit/s)], 8/16 ports [Ethernet(1Gbit/s)]   |   |  |  |  |  |  |
| Maximum System Memory                     | 64 GB   | 64 GB   |  |  |  |  |  |
| Extreme Cache Pool                        |   | 1.6 TB  |  |  |  |  |  |
| Maximum Disk Drives                       | 144   | 144   |  |  |  |  |  |
| Max. no. of drive enclosures              | 5   | 10  |  |  |  |  |  |
| Note                                      | 5 with all 2.5" DE, 10 with all 3.5" DE, 2 with HD-DE or mixture of DEs up to Max no. Drives  |   |  |  |  |  |  |
| Supported RAID levels                     | 0, 1, 1+0, 5, 5+0, 6  |   |  |  |  |  |  |
| Host Interfaces                           | Fibre Channel (16 Gbit/s, 32Gbit/s)<br>iSCSI (10 Gbit/s [10GBase-SR, 10GBase-CR, 10GBase-T], 1 Gbit/s)<br>SAS (12Gbit/s)<br>Ethernet (10 Gbit/s, 1 Gbit/s)  |   |  |  |  |  |  |
| Mixed host interfaces                     | Yes   |   |  |  |  |  |  |
| Max. no. of hosts                         |   | 1,024   |  |  |  |  |  |
| Supported NAS protocols                   | CIFS (SMB 3.1.1), CIFS (SMB 2.0), CIFS (SMB 3.0), NFSv4, NFSv3, NFSv2, FTP, FXP   |   |  |  |  |  |  |
| Maximum Storage Capacity HDD              |   | 2,304 TB  |  |  |  |  |  |
| Maximum Storage Capacity SSD              |   | 4,424 TB  |  |  |  |  |  |
|   | 2.5-inch, SAS, 10,000 rpm (2.4 TB/ 1.8 TB / 1.2 TB / 600 GB / 300 GB*) 2.5-inch, SAS (FIPS), 10,000rpm (1.2TB) 2.5-inch, SSD (30.72TB / 15.36TB / 7.68TB / 3.84TB / 1.92TB / 960GB / 800GB) 2.5-inch, SSD (FIPS) (7.68TB / 3.84TB / 1.92TB) 3.5-inch, Nearline SAS, 7,200rpm (16TB / 14TB / 12TB / 10TB / 8TB / 6TB / 4TB) 3.5-inch, Nearline SAS (FIPS), 7,200rpm (16TB / 12TB / 8TB / 4TB) 3.5-inch, SSD (7.68TB / 3.84TB / 1.92TB / 960GB / 800GB) 3.5-inch, SSD (FIPS, self-encrypting) (3.84TB / 1.92TB) HDDE, Nearline SAS, 7,200rpm (16TB / 14TB / 12 TB / 8TB / 4TB) HDDE, Nearline SAS (FIPS), 7,200rpm (16TB / 12 TB / 8TB / 4TB) |   |  |  |  |  |  |
| Note                                      | ,   | ailable on special request  |  |  |  |  |  |
| Max. no. of SSDs                          | UI  | unlimited   |  |  |  |  |  |
| Mixed 2.5 inch/ 3.5 inch drive enclosures |   | Yes   |  |  |  |  |  |
| Drive interface                           |   | Serial Attached SCSI (12 Gbit/s)  |  |  |  |  |  |
| Back-end disk connectivity                | 1 pair of four-lane x 12 Gbit/s Ser   | 1 pair of four-lane x 12 Gbit/s Serial Attached SCSI buses (SAS 3.0 wide) |  |  |  |  |  |
| Max. no. of RAID groups per system        |   | 72  |  |  |  |  |  |
| Max. no. of LUNs per RAID group           |   | 128   |  |  |  |  |  |
| Max. no. of LUNs                          |   | 4,096   |  |  |  |  |  |
| Max. LUN capacity                         |   | 128 TB  |  |  |  |  |  |
| Max. no. of copy generations              |   | 512   |  |  |  |  |  |
| Performance                               |   |   |  |  |  |  |  |
| Latency                                   |   | ad), 60µsec (Write)   |  |  |  |  |  |
| Sequential access performance             |   | 11,000 MB/s (128KB Read)<br>4,400 MB/s (128KB Write)                      |  |  |  |  |  |
| Random access performance                 | 320,000 IOPS (8KB Read)<br>170,000 IOPS (8KB Write)   |   |  |  |  |  |  |
| Performance management                    |   |   |  |  |  |  |  |
|   |   |   |  |  |  |  |  |

Page 3 / 6 www.fujitsu.com/eternus

| Performance management          |   |  |  |  |  |  |
|---------------------------------|---|--|--|--|--|--|
| Quality of Service              | Yes   |  |  |  |  |  |
| Operation Management Client     | Microsoft Internet Explorer 10, 11#Firefox ESR 60, ESR 68#Microsoft Edge 25, 42, 44#Google Chrome 60, 75#Chrome 47, 50 (Android®)#Safari 8, 9 (iOS)   |  |  |  |  |  |
| Continuity management           | · ·   |  |  |  |  |  |
| Storage Cluster                 | Yes   |  |  |  |  |  |
| Remote Copy functionality       | Synchronous and asynchronous  |  |  |  |  |  |
| Information security management |   |  |  |  |  |  |
| Data confidentiality            | HTTPS (SSL), SSH, CHAP, Bidirectional CHAP  |  |  |  |  |  |
| Data integrity                  | Data Block Guard, Data Encryption, Cache Protection, Disk Drive Patrol, Global Hot Spare, Dedicated Hot Spare, Copy<br>back less, Drive shield, Fast Recovery   |  |  |  |  |  |
| Availability management         |   |  |  |  |  |  |
| Non-disruptive firmware upgrade | Yes   |  |  |  |  |  |
| Hot part replacement            | Yes   |  |  |  |  |  |
| Capacity management             |   |  |  |  |  |  |
| Thin Provisioning               | Yes   |  |  |  |  |  |
| RAID migration                  | Yes   |  |  |  |  |  |
| Reporting function              | Yes   |  |  |  |  |  |
| Hot part expansion              | Yes   |  |  |  |  |  |
| Non-disruptive firmware upgrade | Yes   |  |  |  |  |  |
| Management                      |   |  |  |  |  |  |
| Administration                  | Web-based graphical user interface, CLI (Command Line Interface), ETERNUS SF  |  |  |  |  |  |
| Supported OS for ETERNUS SF     |   |  |  |  |  |  |
| Operation Management Server     | Microsoft® Windows Server® 2016 Microsoft Windows Server 2012, 2012 R2 Solaris® 11 (11/11 or later) Solaris® 10 (except ETERNUS SF Express) Red Hat Enterprise Linux 8 Red Hat® Enterprise Linux® 7 Red Hat® Enterprise Linux® 6 Oracle Linux 6 VMware® vSphere® 6.0, 6.5, 6.7 Microsoft Windows Server 2019 Hyper-V Microsoft Windows Server 2016 Hyper-V Microsoft Windows Server 2012 Hyper-V, 2012 R2 Hyper-V |  |  |  |  |  |
| Operation Management Client     | Microsoft Internet Explorer 10, 11 Firefox ESR 60, ESR 68 Microsoft Edge 25, 42, 44 Google Chrome 60, 75 Chrome® 47, 50 (Android®) Safari 8, 9 (iOS)  |  |  |  |  |  |
| Note                            | See the ETERNUS SF datasheet for further options  |  |  |  |  |  |
| Supported configurations        | All major host operating systems, servers and business applications Detailed support matrix: www.fujitsu.com/global/support/products/computing/storage/disk/supported-configrations   |  |  |  |  |  |
| Installation specification      |   |  |  |  |  |  |
| 19" rackmount                   | Yes   |  |  |  |  |  |
| Power voltage                   | AC 100 - 120 V / AC 200 - 240 V   |  |  |  |  |  |
| Power frequency                 | 50 / 60 Hz  |  |  |  |  |  |
| Power supply efficiency         | 92 % (80 PLUS gold)   |  |  |  |  |  |
| Maximum Power Consumption       | AC 100 - 120 V: 4,170W (4,280VA)  |  |  |  |  |  |
| Maximum Power Consumption       | AC 200 - 240 V: 4,170W (4,280VA)  |  |  |  |  |  |

Page 4 / 6 www.fujitsu.com/eternus

| Installation specification  |   |   |  |  |   |  |  |  |  |
|---|---|---|--|--|---|--|--|--|--|
| Installation specification Power phase                            | Cinalo  |   |  |  |   |  |  |  |  |
| Power pilase  | Single  |   |  |  |   |  |  |  |  |
|   | 2.5-inch Controller<br>Enclosure  | 3.5-inch Controller<br>Enclosure  | 2.5-inch Drive<br>Enclosure                      | 3.5-inch Drive<br>Enclosure                    | High-Density Drive<br>Enclosure                   |  |  |  |  |
| Dimensions (W x D x H)  | 482 x 645 x 88 mm<br>19 x 25.4 x 3.5 inch<br>2 U  | 482 x 670 x 88 mm<br>19 x 26.4 x 3.5 inch<br>2 U  | 482 x 540 x 88 mm<br>19 x 21.3 x 3.5 inch<br>2 U | 482 x 560 x 88 mm<br>19 x 22 x 3.5 inch<br>2 U | 482 x 980 x 176 mm<br>19 x 38.6 x 6.9 inch<br>4 U |  |  |  |  |
| Weight  | 35 kg (77 lb)   | 35 kg (77 lb)   | 35 kg (77 lb)                                    | 35 kg (77 lb)                                  | 100 kg (220 lb)                                   |  |  |  |  |
| Environment   |   |   |  |  |   |  |  |  |  |
| Maximum Heat Generation   |   | AC 100 - 120 V: 15,750: kJ/h<br>AC 200 - 240 V: 15,750: kJ/h  |  |  |   |  |  |  |  |
| Temperature (operating)   | 10 - 40 °C  | 10 - 40 ℃   |  |  |   |  |  |  |  |
| Humidity (operating)  | 20 - 80 %   |   |  |  |   |  |  |  |  |
| Operating environment   | FTS 04230 – Guideline   | FTS 04230 – Guideline for Data Center (installation specification)  |  |  |   |  |  |  |  |
| Operating environment link  | http://docs.ts.fujitsu.c  | http://docs.ts.fujitsu.com/dl.aspx?id=589915e9-1bf8-40f7-8ba4-7cac9371f2f0  |  |  |   |  |  |  |  |
| Compliance  |   |   |  |  |   |  |  |  |  |
| Product safety  | UL 60950-1, CSA 6095  | 50-1, EN 60950-1, IEC 6   | 0950-1, TP TC 004/2011                           | , CNS14336                                     |   |  |  |  |  |
| Electromagnetic Compatibility                                     | FCC Part-15 Class A, IC<br>Class A, KN22  | FCC Part-15 Class A, ICES-003 Class A, EN 55022 (2010), +AI, VCCI Class A, AS/NZS CISPR 22 Class A, CNS13438 (C6357 Class A, KN22 |  |  |   |  |  |  |  |
| Electromagnetic Immunity  | EN 55024  | EN 55024  |  |  |   |  |  |  |  |
| Environmental compliance  | RoHS compliant, WEE   | RoHS compliant, WEEE compliant  |  |  |   |  |  |  |  |
| Compliance notes  | There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. |   |  |  |   |  |  |  |  |
| Compliance link   | https://sp.ts.fujitsu.com/sites/certificates  |   |  |  |   |  |  |  |  |
| Warranty  |   |   |  |  |   |  |  |  |  |
| Warranty period   | 3 years   | 3 years   |  |  |   |  |  |  |  |
| Warranty type   | Onsite warranty   | Onsite warranty   |  |  |   |  |  |  |  |
| Warranty Terms & Conditions Product Support Services - the perfec | www.fujitsu.com/warr<br>ct extension  | ranty   |  |  |   |  |  |  |  |
| Support Pack Options  | Available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country)   |   |  |  |   |  |  |  |  |
| Recommended Service   | 24x7, Onsite Respons  | 24x7, Onsite Response Time: 4h  |  |  |   |  |  |  |  |
| Service Lifecycle   | 5 years after end of p  | 5 years after end of product life   |  |  |   |  |  |  |  |
| Service Weblink   | www.fujitsu.com/serv  | ices/product-services   |  |  |   |  |  |  |  |

Page 5 / 6 www.fujitsu.com/eternus

#### Fujitsu products, solutions & services

In addition to FUJITSU ETERNUS DX100 S5, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### **Computing Products**

www.fujitsu.com/global/products/computing/

#### Software

www.fujitsu.com/software/

#### More information

Learn more about Fujitsu ETERNUS DX100 S5, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/eternus

#### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/qlobal/about/environment



#### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html

Copyright 2020 FUJITSU LIMITED

#### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

FUJITSU LIMITED Website: www.fujitsu.com/eternus 2020-09-07 WW-EN

Page 6 / 6 www.fujitsu.com/eternus