ThinkStation P340 Tower 30DH00H9GE

Product

ThinkStation P340 Tower

Region

WE

Country/Region

Germany

Machine Type

30DH

TopSeller

TopSeller

Processor

Intel Core i9-10900K (10C / 20T, 3.7 / 5.3GHz, 20MB)

Integrated Graphics

Intel UHD Graphics 630

Discrete Graphics

NVIDIA Quadro RTX 5000 16GB

Chipset

Intel W480

HDD Controller

Onboard Intel RST SATA RAID

M.2 SSD RAID Controller

Onboard Intel RSTe PCIe

Memory

2x 32GB UDIMM DDR4-2933 non-ECC

Internal Disk Drive

None

M.2 SSD Drive

1x 1TB SSD M.2 PCIe NVMe Opal

Optane Memory

None

Optical

9.0mm DVD±RW

Media Reader

SD Reader

Onboard Ethernet

1x GbE RJ-45

Additional Ethernet

None

WLAN + Bluetooth

None

Optional Rear Ports

None

Chassis Intrusion Switch

Chassis Intrusion Switch

Cover Lock

E-Lock

Cable Lock

Cable Lock

Keyboard

USB Traditional Keyboard, Black, German

Vouse

USB Calliope Mouse

Power Supply

500W 92%

System Management

Intel vPro with AMT 14

Operating System

Windows 10 Pro 64, German

Bundled Software

None

Base Warranty

3-year, Onsite

Bundled Service

None

EAN/UPC/JAN

0195235605745

End of Support

2028-07-30

Announce Date

2020-07-17

Recommended Services

Best

5Y Premier Support Upgrade from 3Y Onsite (5WS0T36135)

Pottor

4Y Premier Support Upgrade from 3Y Onsite (5WS0T36136)

Good

3Y Premier Support Upgrade from 3Y Onsite (5WS0U26646)

WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



https://psref.lenovo.com

Visit psref website for the latest version of Product specifications Reference.
© Lenovo, 2020. All rights reserved.



ThinkStation P340 Tower Platform Specifications

Components	Specification																		
Form factor	17L Tower																		
Dimensions	Height: 376 mm (14.8 in). Width: 170 mm (6.7 in). Depth: 315.35 mm (12.4 in)																		
Weight	Ctr																		
	Maximum configuration: 20.7 lb (9.4 kg)																		
Processor Sockets			:0 :7 :	- · · · · · ·															
Processor Support		i, Core	19, 17, 1		rocesso	r													
	Processor Number	Cores T	hreads	Base Frequency	, Cache	TDP	Memory Types	ECC	Processor Graphics	vPro									
	Xeon W-1290P	10	20	3.7GHz	20MB	125W	DDR4-2933	Yes	UHD P630	Yes									
	Xeon W-1290	10	20	3.2GHz	20MB		DDR4-2933		UHD P630										
	Xeon W-1270P	8	16	3.8GHz			DDR4-2933		UHD P630	Yes Yes									
	Xeon W-1270	8	16	3.4GHz	16MB	80W	DDR4-2933	Yes	UHD P630	Yes									
	Xeon W-1250P	6	12	4.1GHz	12MB	125W	DDR4-2666	Yes	UHD P630	Yes									
	Xeon W-1250	6	12	3.3GHz			DDR4-2666		UHD P630	Yes									
	Core i9-10900K	10	20	3.7GHz			DDR4-2933		UHD 630	Yes									
Processor	Core i9-10900	10	20	2.8GHz			DDR4-2933		UHD 630	Yes									
	Core i7-10700K	8	16	3.8GHz			DDR4-2933		UHD 630	Yes									
	Core i7-10700	8	16	2.9GHz			DDR4-2933		UHD 630	Yes									
	Core i5-10600K Core i5-10600	6	12 12	4.1GHz 3.3GHz			DDR4-2666 DDR4-2666		UHD 630 UHD 630	Yes Yes									
	Core i5-10500	6	12	3.1GHz			DDR4-2666		UHD 630	Yes									
	Core i5-10400	6	12	2.9GHz	12MB		DDR4-2666		UHD 630	No									
	Core i3-10320	4	8	3.8GHz	8MB		DDR4-2666		UHD 630	No									
	Core i3-10300	4	8	3.7GHz	8MB		DDR4-2666		UHD 630	No									
	Core i3-10100	4	8	3.6GHz	6MB		DDR4-2666		UHD 630	No									
Chipset	Intel W480 Chip	set						,											
Memory Sockets	4 DIMM sockets with 2 channels																		
•					FCC														
Memory Types	8GB/16GB/32GB DDR4-2933 UDIMM ECC, or 4GB/8GB/16GB/32GB DDR4-2933 UDIMM non-ECC																		
Memory Capacity	128GB	0.2,02	<u> </u>		02														
		nory ar	nd ECC	-anahla (PII are	neer	lad												
Wichiory Frotection	ECC. ECC memory and ECC-enable CPU are needed Three PCIe 3.0 slots as following:																		
Expansion slots	Slot 1 PCIe 3.0 x16, full height, full length, links to CPU																		
Expansion siots	Slot 2 PCIe 3.0	x1, ful	l height	t, full leng	ıth, links	to Po	CH												
	Slot 3 PCle 3.0	x16 (n	egotial	ole link wi	dth x4),	full h	eight, full le	ngth,	links to Po	CH (
	Slot 3 PCIe 3.0 x16 (negotiable link width x4), full height, full length, links to PCH Integrated Intel UHD Graphics P630 in Xeon processors, or Intel UHD Graphics 630																		
	in Core processors.																		
Processor graphics	Works along with discrete graphics to support multi-display, enables three rear																		
,	display connect		DP sta	ndard, 1 v	video po	ort opt	ional (Vide	o por	t can be D	P, -									
	HDMI, or USB-	C)																	
	Graphics	3	Me	mory	Power		Conne	ector		Max									
										Qty									
Discrete Graphics Offering	Quadro P400	2GB GDI			30W	3x miniDP			2										
	Quadro P620		2GB GDDF		40W		4x miniDP			2									
	Quadro P1000		4GB GDDF		50W		4x miniDP		2										
	Quadro P2200																		
	Quadro RTX 40						3x DP, 1x VirtualLink			1									
	addition to the design of the second								_1_										
		Notes: RTX 4000/RTX 5000/2x P2200 needs 500W PSU.																	
		X 5000/2	x P2200	needs 500V	PSU.														
	Notes: RTX 4000/RT		2x P2200	needs 500V	_	face	Disk Tv	/pe	RAID	7 1									
Storage	Notes: RTX 4000/RT	ller		Туре	Inter				RAID 0/1/10/5	 									
Storage Controller	Notes: RTX 4000/RT	oller RST SA	ATA RA	Type ID Std	Inter SATA	6Gb/s		SSD	0/1/10/5										

	Components	Specification									
	7		terface	RPM	Offering	Max Qty					
j	1		TA 6Gb/s		1TB/2TB/4TB/6TB	2					
4	Storage Support		ΓA 6Gb/s		1TB FIPS	4					
_	3		ΓA 6Gb/s		512GB/1TB	4					
_	-		le NVMe	-	256GB/512GB/1TB/2TB	4					
_		Bay 1 First 3.5" disk bay									
)		Bay 2 First 2.5" SATA bay									
		Bay 3 Secondary 3.5	" disk bay	/							
_	Storage Bays										
		Bay 5 9mm Slim ODI	D bay								
		Bay 6 Media reader									
		M.2 4x M.2 SSD (2 onboard. 2 via PCIe to M.2 adapter)									
_	Media reader	Optional SD reader on most models									
-	Network	One onboard GbE port via integrated gigabit ethernet Intel i219LM, supports									
j	interfaces	Wake-on-LAN. Optional PCIe ethernet adapters are available									
	WLAN + Bluetooth	Optional Intel Wi-Fi 6 AX201, 2x2, 2.4GHz/5GHz (160MHz channels), WiFi 6, Bluetooth 5									
	Security features	Power-on and admin password. Trusted Platform Module, TCG 2.0 compliant. Optional chassis intrusion switch, E-lock, cable lock, Kensington lock, and pad lock									
	Intel vPro	Supports Intel vPro on Xeon and selected Core i7 or i5 models. vPro also requires AX201 if Wi-Fi function is needed									
	Intel AMT	Intel Active Management Technology 14 on vPro models, Intel Standard Manageability on other models									
	Base warranty	Most models comes with 3-year limited onsite service with 9x5/NBD. Other models may have 1 or 2-year limited onsite service									
	HD Audio										
	Front ports	2x USB-A 3.2 Gen 1. 2x USB-A 3.2 Gen 2. 1x USB-C 3.2 Gen 1. 1x Mic-in. 1x Combo jack									
٦	Rear ports	2x USB-A 3.2 Gen 1. 2x USB-A 2.0. 1x RJ-45. 1x COM. 2x DP. 1x Audio line-out									
0	Optional rear ports	Supports the following via cable: 1x COM. 1x Parallel. 2x PS/2. 1x video (DP, HDMI, or USB-C). 2x USB 2.0. Supports the following via PCle adapter: 4x COM*. 1x USB-C 3.2 Gen 2. 2x USB-A 3.2 Gen 1*. 1x Thunderbolt Notes: 4x COM and 2x USB-A 3.2 Gen 1 are special bids only.									
	Temperature	Operating: 50 °F to 95 °F (10 °C to 35 °C) Non operating (no package): 14 °F to 140 °F (-10 °C to 60 °C) Non operating (with package): -40 °F to 140 °F (-40 °C to 60 °C)									
	Altitude	Operating: -15.2 m (-50 ft) to 3048 m (10 000 ft). Storage: -15.2 m (-50 ft) to 10, 668 m (35 000 ft)									
	Humidity	Operating: 30%~90%, non-condensing Storage (with package): 20%~90%, non-condensing									
	Environmental certification	RoHS-compliant, EPEAT Silver rating, and ENERGY STAR 8 qualified									
_	Power supply	Supports one of the following: 300W, 90% PSU, 100V - 240V, 80 PLUS Gold qualified 500W, 92% PSU, 100V - 240V, 80 PLUS Platinum qualified									
		Please visit www.think	<u>kworkstat</u>	ions.c	om/isv-certifications/						
	Note: 1. Depending on many t	actors, actual data transfer so	eed mentior	ned on t	his page may be lower than theoretica	al speed					

pending on many factors, actual data transfer speed mentioned on this page may be lower than theoretical speed.

ny questions or advice on ThinkStation PSREF, please contact Lenovo workstation PSREF developer











