

# ThinkStation P330 Tower Gen 2 30CY003KGE

**Product**

ThinkStation P330 Tower Gen 2

**Region**

WE

**Country/Region**

Germany

**Machine Type**

30CY

**TopSeller**

TopSeller

**Processor**

Core i7-9700K 8C/8T/3.6GHz/12MB/95W/DDR4-2666

**Memory**

2x 8GB UDIMM DDR4-2666 Non-ECC

**Processor Graphics**

Intel UHD Graphics 630

**Discrete Graphics Card**

1x NVIDIA Quadro P2200 5GB 4x DP

**Monitor Cable**

None

**Storage Controller**

Onboard Intel RST SATA RAID

**M.2 SSD RAID Controller**

Onboard Intel RST PCIe RAID

**Internal Disk**

None

**Optane Memory**

None

**M.2 SSD Drive**

1x 512GB SSD M.2 PCIe NVMe Opal

**Optical**

9.0mm DVD±RW

**Media Reader**

SD Reader

**HD Audio**

Onboard Realtek ALC233

**WLAN + Bluetooth**

None

**Available Networking Port**

1x GbE RJ-45

**Chassis Intrusion Switch**

Chassis Intrusion Switch

**Cable Lock**

None

**E-Lock**

E-Lock

**Dust Filter**

None

**Optional 1394 Port**

None

**Optional Parallel Port**

None

**Optional Thunderbolt Port**

None

**Optional Serial Port**

None

**Optional USB Port**

None

**Optional eSATA Port**

None

**Optional PS/2 Port**

None

**Optional Video Port**

None

**Keyboard**

USB Traditional Keyboard, Germany

**Mouse**

USB Calliope Mouse

**Power Supply**

400W Platinum Fixed

**System Management**

Standard Manageability

**Operating System**

Windows 10 Pro 64, German

**Bundled Software**

None

**Base Warranty**

3-year, Onsite

**Bundled Service**

None

**Global**

No

**End of Support**

2025-08-23

**Announce Date**

2019-07-23

**Recommended Services****Best**

5Y Premier Support Upgrade from 3Y Onsite (5WS0T36135)

**Better**

4Y Premier Support Upgrade from 3Y Onsite (5WS0T36136)

**Good**

3Y Premier Support Upgrade from 3Y Onsite (5WS0U26646)

[WWW.LENOVO.COM](http://WWW.LENOVO.COM)

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<https://psref.lenovo.com>

Visit psref website for the latest version of Product Specifications Reference.

© Lenovo, 2019. All rights reserved.



Lenovo™

# ThinkStation P330 Tower Gen 2 (30CY and 30D0) Platform Specifications - I of II




Components	Specification																																																																																	
Form factor	18L Tower																																																																																	
Dimensions	Height: 376 mm (14.8 in). Width: 165 mm (6.5 in). Depth: 328 mm (12.9 in)																																																																																	
Weight	Maximum configuration: 28.22 lb (12.8kg)																																																																																	
Processor	Supports one of the following processors:																																																																																	
	<table border="1"> <tbody> <tr> <td>Xeon E-2286G</td> <td>6C/12T/4.0GHz/12MB/95W/DDR4-2666</td> <td>400W PSU needed</td> </tr> <tr> <td>Xeon E-2278G</td> <td>8C/16T/3.4GHz/16MB/80W/DDR4-2666</td> <td>400W PSU needed</td> </tr> <tr> <td>Xeon E-2276G</td> <td>6C/12T/3.8GHz/12MB/80W/DDR4-2666</td> <td></td> </tr> <tr> <td>Xeon E-2274G</td> <td>4C/8T/4.0GHz/8MB/83W/DDR4-2666</td> <td></td> </tr> <tr> <td>Xeon E-2246G</td> <td>6C/12T/3.6GHz/12MB/80W/DDR4-2666</td> <td></td> </tr> <tr> <td>Xeon E-2244G</td> <td>4C/8T/3.8GHz/8MB/71W/DDR4-2666</td> <td></td> </tr> <tr> <td>Xeon E-2236</td> <td>6C/12T/3.4GHz/12MB/80W/DDR4-2666</td> <td></td> </tr> <tr> <td>Xeon E-2234</td> <td>4C/8T/3.6GHz/8MB/71W/DDR4-2666</td> <td></td> </tr> <tr> <td>Xeon E-2226G</td> <td>6C/6T/3.4GHz/12MB/80W/DDR4-2666</td> <td></td> </tr> <tr> <td>Xeon E-2224G</td> <td>4C/4T/3.5GHz/8MB/71W/DDR4-2666</td> <td></td> </tr> <tr> <td>Xeon E-2224</td> <td>4C/4T/3.4GHz/8MB/71W/DDR4-2666</td> <td></td> </tr> <tr> <td>Xeon E-2186G</td> <td>6C/12T/3.8GHz/12MB/95W/DDR4-2666</td> <td>400W PSU needed</td> </tr> <tr> <td>Xeon E-2174G</td> <td>4C/8T/3.8GHz/8MB/71W/DDR4-2666</td> <td></td> </tr> <tr> <td>Pentium Gold G5620</td> <td>2C/4T/4.0GHz/4MB/54W/DDR4-2400</td> <td></td> </tr> <tr> <td>Core i9-9900</td> <td>8C/16T/3.1GHz/16MB/65W/DDR4-2666</td> <td></td> </tr> <tr> <td>Core i7-9700K</td> <td>8C/8T/3.6GHz/12MB/95W/DDR4-2666</td> <td>400W PSU needed</td> </tr> <tr> <td>Core i7-9700</td> <td>8C/8T/3.0GHz/12MB/65W/DDR4-2666</td> <td></td> </tr> <tr> <td>Core i7-8700</td> <td>6C/12T/3.2GHz/12MB/65W/DDR4-2666</td> <td></td> </tr> <tr> <td>Core i5-9600K</td> <td>6C/6T/3.7GHz/9MB/95W/DDR4-2666</td> <td>400W PSU needed</td> </tr> <tr> <td>Core i5-9600</td> <td>6C/6T/3.1GHz/9MB/65W/DDR4-2666</td> <td></td> </tr> <tr> <td>Core i5-9500</td> <td>6C/6T/3.0GHz/9MB/65W/DDR4-2666</td> <td></td> </tr> <tr> <td>Core i5-9400</td> <td>6C/6T/2.9GHz/9MB/65W/DDR4-2666</td> <td></td> </tr> <tr> <td>Core i5-8500</td> <td>6C/6T/3.0GHz/9MB/65W/DDR4-2666</td> <td></td> </tr> <tr> <td>Core i3-9300</td> <td>4C/4T/3.7GHz/8MB/62W/DDR4-2400</td> <td></td> </tr> <tr> <td>Core i3-9100</td> <td>4C/4T/3.6GHz/6MB/65W/DDR4-2400</td> <td></td> </tr> <tr> <td>Core i3-8300</td> <td>4C/4T/3.7GHz/8MB/62W/DDR4-2400</td> <td></td> </tr> <tr> <td>Core i3-8100</td> <td>4C/4T/3.6GHz/6MB/65W/DDR4-2400</td> <td></td> </tr> </tbody> </table>	Xeon E-2286G	6C/12T/4.0GHz/12MB/95W/DDR4-2666	400W PSU needed	Xeon E-2278G	8C/16T/3.4GHz/16MB/80W/DDR4-2666	400W PSU needed	Xeon E-2276G	6C/12T/3.8GHz/12MB/80W/DDR4-2666		Xeon E-2274G	4C/8T/4.0GHz/8MB/83W/DDR4-2666		Xeon E-2246G	6C/12T/3.6GHz/12MB/80W/DDR4-2666		Xeon E-2244G	4C/8T/3.8GHz/8MB/71W/DDR4-2666		Xeon E-2236	6C/12T/3.4GHz/12MB/80W/DDR4-2666		Xeon E-2234	4C/8T/3.6GHz/8MB/71W/DDR4-2666		Xeon E-2226G	6C/6T/3.4GHz/12MB/80W/DDR4-2666		Xeon E-2224G	4C/4T/3.5GHz/8MB/71W/DDR4-2666		Xeon E-2224	4C/4T/3.4GHz/8MB/71W/DDR4-2666		Xeon E-2186G	6C/12T/3.8GHz/12MB/95W/DDR4-2666	400W PSU needed	Xeon E-2174G	4C/8T/3.8GHz/8MB/71W/DDR4-2666		Pentium Gold G5620	2C/4T/4.0GHz/4MB/54W/DDR4-2400		Core i9-9900	8C/16T/3.1GHz/16MB/65W/DDR4-2666		Core i7-9700K	8C/8T/3.6GHz/12MB/95W/DDR4-2666	400W PSU needed	Core i7-9700	8C/8T/3.0GHz/12MB/65W/DDR4-2666		Core i7-8700	6C/12T/3.2GHz/12MB/65W/DDR4-2666		Core i5-9600K	6C/6T/3.7GHz/9MB/95W/DDR4-2666	400W PSU needed	Core i5-9600	6C/6T/3.1GHz/9MB/65W/DDR4-2666		Core i5-9500	6C/6T/3.0GHz/9MB/65W/DDR4-2666		Core i5-9400	6C/6T/2.9GHz/9MB/65W/DDR4-2666		Core i5-8500	6C/6T/3.0GHz/9MB/65W/DDR4-2666		Core i3-9300	4C/4T/3.7GHz/8MB/62W/DDR4-2400		Core i3-9100	4C/4T/3.6GHz/6MB/65W/DDR4-2400		Core i3-8300	4C/4T/3.7GHz/8MB/62W/DDR4-2400		Core i3-8100	4C/4T/3.6GHz/6MB/65W/DDR4-2400	
	Xeon E-2286G	6C/12T/4.0GHz/12MB/95W/DDR4-2666	400W PSU needed																																																																															
	Xeon E-2278G	8C/16T/3.4GHz/16MB/80W/DDR4-2666	400W PSU needed																																																																															
	Xeon E-2276G	6C/12T/3.8GHz/12MB/80W/DDR4-2666																																																																																
	Xeon E-2274G	4C/8T/4.0GHz/8MB/83W/DDR4-2666																																																																																
	Xeon E-2246G	6C/12T/3.6GHz/12MB/80W/DDR4-2666																																																																																
	Xeon E-2244G	4C/8T/3.8GHz/8MB/71W/DDR4-2666																																																																																
	Xeon E-2236	6C/12T/3.4GHz/12MB/80W/DDR4-2666																																																																																
	Xeon E-2234	4C/8T/3.6GHz/8MB/71W/DDR4-2666																																																																																
	Xeon E-2226G	6C/6T/3.4GHz/12MB/80W/DDR4-2666																																																																																
	Xeon E-2224G	4C/4T/3.5GHz/8MB/71W/DDR4-2666																																																																																
	Xeon E-2224	4C/4T/3.4GHz/8MB/71W/DDR4-2666																																																																																
	Xeon E-2186G	6C/12T/3.8GHz/12MB/95W/DDR4-2666	400W PSU needed																																																																															
	Xeon E-2174G	4C/8T/3.8GHz/8MB/71W/DDR4-2666																																																																																
	Pentium Gold G5620	2C/4T/4.0GHz/4MB/54W/DDR4-2400																																																																																
	Core i9-9900	8C/16T/3.1GHz/16MB/65W/DDR4-2666																																																																																
	Core i7-9700K	8C/8T/3.6GHz/12MB/95W/DDR4-2666	400W PSU needed																																																																															
	Core i7-9700	8C/8T/3.0GHz/12MB/65W/DDR4-2666																																																																																
	Core i7-8700	6C/12T/3.2GHz/12MB/65W/DDR4-2666																																																																																
	Core i5-9600K	6C/6T/3.7GHz/9MB/95W/DDR4-2666	400W PSU needed																																																																															
	Core i5-9600	6C/6T/3.1GHz/9MB/65W/DDR4-2666																																																																																
	Core i5-9500	6C/6T/3.0GHz/9MB/65W/DDR4-2666																																																																																
	Core i5-9400	6C/6T/2.9GHz/9MB/65W/DDR4-2666																																																																																
	Core i5-8500	6C/6T/3.0GHz/9MB/65W/DDR4-2666																																																																																
Core i3-9300	4C/4T/3.7GHz/8MB/62W/DDR4-2400																																																																																	
Core i3-9100	4C/4T/3.6GHz/6MB/65W/DDR4-2400																																																																																	
Core i3-8300	4C/4T/3.7GHz/8MB/62W/DDR4-2400																																																																																	
Core i3-8100	4C/4T/3.6GHz/6MB/65W/DDR4-2400																																																																																	
Chipset	Intel C246 Chipset																																																																																	
Memory Sockets	4 DIMM sockets with 2 channels																																																																																	
Memory Types	8GB/16GB DDR4-2666 UDIMM ECC or 4GB/8GB/16GB DDR4-2666 UDIMM non-ECC																																																																																	
Memory Capacity	64B with 4 x 16GB, both UDIMM ECC or UDIMM non-ECC																																																																																	
Memory Protection	ECC on models with UDIMM ECC memory																																																																																	
Expansion slots	Three PCIe 3.0 slots as following:																																																																																	
	Slot 1 PCIe 3.0 x16, full height, half length, links to CPU																																																																																	
	Slot 2 PCIe 3.0 x1, full height, full length, links to PCH																																																																																	
	Slot 3 PCIe 3.0 x16 (negotiable link width x4), full height, half length, links to PCH																																																																																	
Processor graphics	Integrated Intel UHD Graphics P630 in -G suffix Xeon processors, or Intel UHD Graphics 630 in Core i7, i5, i3, or Pentium processors. Works along with discrete graphics to support multi-display, enables three rear display connectors (2 DP standard, 1 DP or HDMI optional)																																																																																	
Discrete Graphics Offering	Up to two PCIe 3.0 x16 slots for discrete graphics card (Slot 1 and 3). Supports the following graphics adapters:																																																																																	
	<table border="1"> <thead> <tr> <th>Graphics</th> <th>Memory</th> <th>Power</th> <th>Connector</th> <th>Max Qty</th> </tr> </thead> <tbody> <tr> <td>Quadro P400</td> <td>2GB GDDR5</td> <td>30W</td> <td>3x miniDP</td> <td>2</td> </tr> <tr> <td>Quadro P620</td> <td>2GB GDDR5</td> <td>40W</td> <td>4x miniDP</td> <td>2</td> </tr> <tr> <td>Quadro P1000</td> <td>4GB GDDR5</td> <td>50W</td> <td>4x miniDP</td> <td>2</td> </tr> <tr> <td>Quadro P2000</td> <td>5GB GDDR5</td> <td>75W</td> <td>4x DP</td> <td>2</td> </tr> <tr> <td>Quadro P2200</td> <td>5GB GDDR5X</td> <td>75W</td> <td>4x DP</td> <td>2</td> </tr> <tr> <td>Quadro P5000</td> <td>16GB GDDR5X</td> <td>180W</td> <td>DVI-D DL + 4x DP</td> <td>1</td> </tr> <tr> <td>Quadro RTX 4000</td> <td>8GB GDDR6</td> <td>160W</td> <td>3x DP, 1x VirtualLink</td> <td>1</td> </tr> </tbody> </table>	Graphics	Memory	Power	Connector	Max Qty	Quadro P400	2GB GDDR5	30W	3x miniDP	2	Quadro P620	2GB GDDR5	40W	4x miniDP	2	Quadro P1000	4GB GDDR5	50W	4x miniDP	2	Quadro P2000	5GB GDDR5	75W	4x DP	2	Quadro P2200	5GB GDDR5X	75W	4x DP	2	Quadro P5000	16GB GDDR5X	180W	DVI-D DL + 4x DP	1	Quadro RTX 4000	8GB GDDR6	160W	3x DP, 1x VirtualLink	1																																									
	Graphics	Memory	Power	Connector	Max Qty																																																																													
	Quadro P400	2GB GDDR5	30W	3x miniDP	2																																																																													
	Quadro P620	2GB GDDR5	40W	4x miniDP	2																																																																													
	Quadro P1000	4GB GDDR5	50W	4x miniDP	2																																																																													
	Quadro P2000	5GB GDDR5	75W	4x DP	2																																																																													
	Quadro P2200	5GB GDDR5X	75W	4x DP	2																																																																													
	Quadro P5000	16GB GDDR5X	180W	DVI-D DL + 4x DP	1																																																																													
	Quadro RTX 4000	8GB GDDR6	160W	3x DP, 1x VirtualLink	1																																																																													
<i>Note: 2x Quadro P2000, Quadro P5000, or Quadro RTX 4000 needs 400W PSU</i>																																																																																		

Components	Specification																														
Storage Controller	Storage Controller																														
	Onboard Intel RST SATA RAID																														
	Onboard Intel RST PCIe RAID																														
Storage Support	<table border="1"> <thead> <tr> <th>Disk Type</th> <th>Interface</th> <th>RPM</th> <th>Offering</th> <th>Max Qty</th> </tr> </thead> <tbody> <tr> <td>3.5" SATA HDD</td> <td>SATA 6Gb/s</td> <td>7.2K</td> <td>1TB/2TB/4TB</td> <td>3</td> </tr> <tr> <td>2.5" SATA HDD</td> <td>SATA 6Gb/s</td> <td>7.2K</td> <td>500GB FIPS</td> <td>4</td> </tr> <tr> <td>2.5" SATA SSD</td> <td>SATA 6Gb/s</td> <td></td> <td>256GB/512GB/1TB</td> <td>4</td> </tr> <tr> <td>Optane Memory</td> <td>PCIe NVMe</td> <td></td> <td>32GB</td> <td>1, used with HDD/SSD</td> </tr> <tr> <td>M.2 PCIe SSD</td> <td>PCIe NVMe</td> <td></td> <td>256GB/512GB/1TB</td> <td>3</td> </tr> </tbody> </table>	Disk Type	Interface	RPM	Offering	Max Qty	3.5" SATA HDD	SATA 6Gb/s	7.2K	1TB/2TB/4TB	3	2.5" SATA HDD	SATA 6Gb/s	7.2K	500GB FIPS	4	2.5" SATA SSD	SATA 6Gb/s		256GB/512GB/1TB	4	Optane Memory	PCIe NVMe		32GB	1, used with HDD/SSD	M.2 PCIe SSD	PCIe NVMe		256GB/512GB/1TB	3
	Disk Type	Interface	RPM	Offering	Max Qty																										
	3.5" SATA HDD	SATA 6Gb/s	7.2K	1TB/2TB/4TB	3																										
	2.5" SATA HDD	SATA 6Gb/s	7.2K	500GB FIPS	4																										
	2.5" SATA SSD	SATA 6Gb/s		256GB/512GB/1TB	4																										
	Optane Memory	PCIe NVMe		32GB	1, used with HDD/SSD																										
M.2 PCIe SSD	PCIe NVMe		256GB/512GB/1TB	3																											
Storage Bays	Up to five bays with four disk bays plus one slim optical bay, supports up to 3x 3.5" HDD plus 1x 2.5" SSD, or 4x 2.5" HDD/SSD																														
	Bay 1 Primary disk bay, 3.5" or 2.5"																														
	Bay 2 2.5" SATA bay, cannot be available when 2nd Quadro P2000 is used																														
	Bay 3 Secondary disk bay, 3.5" or 2.5"																														
	Bay 4 5.25" Flex bay, supports one of the following: <ul style="list-style-type: none"> <li>Flex module for optional front eSATA/Thunderbolt/IEEE1394</li> <li>3rd disk bay, 3.5" or 2.5", removable, via Front Access Storage Enclosure, using SATA 4 connector as eSATA mode</li> <li>3rd disk bay, 3.5" or 2.5", via 5.25" to 3.5" HDD Kit</li> </ul>																														
	Bay 5 9mm Slim ODD bay																														
M.2 3x M.2 SSD (1 onboard, 2 via PCIe to M.2 adapter)																															
Media reader	Optional SD card reader on most models																														
Network interfaces	One onboard GbE port via integrated gigabit ethernet Intel i219LM, supports Wake-on-LAN. Optional PCIe ethernet adapters are available																														
WLAN + Bluetooth	One dedicated onboard M.2 slot for optional Intel Wireless-AC 9560, 2x2, 2.4GHz/5GHz (160MHz channels), 802.11ac, Bluetooth 5, up to 1.73Gbps																														
Security features	Power-on and admin password. Trusted Platform Module, TCG 2.0 compliant. Optional chassis intrusion switch, e-lock, cable lock, Kensington lock, and pad lock																														
Intel vPro	Supports Intel vPro on Xeon models. vPro also requires Wireless-AC 9560 if Wi-Fi is needed																														
Intel AMT	Intel Active Management Technology 12 on Xeon models, Intel Standard Manageability on other models																														
Base warranty	US models comes with 3-year limited onsite service with 9x5/NBD. 1 or 3-year limited onsite service with 9x5/NBD in EMEA or other GEOs																														
HD Audio	Intel HD Audio interface with Realtek ALC233 Codec																														
Front ports	2x USB 3.1 Gen 1 Type A. 2x USB 3.1 Gen 2 Type A. 1x USB 3.1 Gen 1 Type-C. 1x Mic-in. 1x Combo jack																														
Rear ports	2x USB 3.1 Gen 1 Type A. 2x USB 2.0 Type-A. 1x RJ-45. 1x COM. 2x DP. 1x Audio line-out <i>Notes: DP needs Core, Pentium, or -G suffix Xeon processor</i>																														
Optional front ports (on flex module)	2x Thunderbolt (USB Type-C), one of two ports supports video-out. 1x eSATA. 1x IEEE1394																														
Optional rear ports	Supports the following via cable: 1x COM. 1x Parallel. 2x PS/2. 1x DP or 1x HDMI. 2x USB 2.0 Supports the following via PCIe adapter: 4x COM. 2x USB 3.1 Type-C. 2x USB 3.0. 1x Thunderbolt. <i>Notes: DP or HDMI needs Core, Pentium, or -G suffix Xeon processor</i>																														
Temperature	Operating: 50 °F to 95 °F (10 °C to 35 °C) Non operating (no package): 14 °F to 140 °F (-10 °C to 60 °C) Non operating (with package): -40 °F to 140 °F (-40 °C to 60 °C)																														

Components	Specification
Altitude	Operating: -15.2 m (-50 ft) to 3048 m (10 000 ft). Storage: -15.2 m (-50 ft) to 10, 668 m (35 000 ft)
Humidity	Operating: 30%~90%, non-condensing Storage (with package): 20%~90%, non-condensing
Environmental certification	RoHS-compliant. GREENGUARD. EPEAT Silver rating and ENERGY STAR 7 qualified
Power supply	Supports one 250W or 400W power supply, 100V - 240V, 92% PSU. Climate Savers Computing Platinum and 80 PLUS Platinum qualified. 400W PSU supports one 6+2-pin aux power connector.
ISV certifications	Please visit <a href="http://www.thinkworkstations.com/isv-certifications/">www.thinkworkstations.com/isv-certifications/</a>

Note:  
 1. Depending on many factors, actual data transfer speed mentioned on this page may be lower than theoretical speed.  
 2. Any questions or advice on ThinkStation PSREF, please contact [ThinkStation PSREF developer](#)



# ThinkStation P330 Tower Gen 2

