

Data Sheet

Fujitsu PSAS CP400i SAS Controller

PSAS CP400i, 8-port, 12Gb/s SAS+SATA PCIe Host Bus Adapter

The SAS / SATA technology offers a performance improvement over traditional SCSI connections. Serial Attached SCSI (SAS) and Serial ATA (SATA) are point-to-point serial peripheral interfaces in which controllers are linked directly to disk drives. This technology supports full-duplex signal transmission up to 12Gb/s.

SAS devices can communicate with both SAS and SATA devices. A key difference between SAS and SATA devices is, that SAS devices can have two data ports, of which each resides in a different SAS domain. This enables complete failover redundancy. If one path fails, there is still communication along a separate and independent path.

PSAS CP400i

The PSAS CP400i, eight port SAS/SATA host bus adapter provides increased connectivity and maximum performance for high-end servers and applications within internal storage. Performance is based on the LSI SAS3008 IO controller, integrating the latest enhancements in SAS and PCI Express 3.0 technology.

The PSAS CP400i provides two x4 internal SFF8643 (Mini-SAS HD), enabling a low profile solution that can achieve over 1 million IOPs. The PSAS CP400i adapter is backwards compatible with previous SAS and PCI generations through automatic negotiation and provides SAS data transfer rates of 12, 6 and 3Gb/s per lane and SATA data transfer rates of 6 and 3Gb/s per lane.

There is also an order option with separate order code for LTO which is otherwise functionally identical.



Main Features	Benefits
<ul style="list-style-type: none"> ■ 12Gb/s data transfer rate per port ■ Two x4 internal SFF8643 (Mini-SAS HD) connectors ■ LSI SAS3008 IO Controller's Fusion-MPT™ 2.0 architecture can achieve more than 1,000,000 I/Os per second ■ MD2 low profile form-factor design 	<ul style="list-style-type: none"> ■ 12Gb/s SAS connectivity eases integration and broadens application by supporting legacy speeds and the SATA protocol ■ Doubles the performance of previous generation SATA+SAS HBAs ■ Environmentally friendly due to low-power consumption ■ MD2 form factor ideal for 1U and 2U server

Technical details

Technical details

Controller Silicon	LSI SAS3008
Controller type	SAS Ctrl.
Operating system	Information to released operating systems can be found in the server datasheets. Details can be found in the released drivers list on the support portal.
Released drivers list link	http://support.ts.fujitsu.com/Download/Index.asp
Number of ports	8 ports int.
Connector internal	2x SFF8643 (Mini-SAS HD)
Bus interface	PCIe 3.0 x8
RAID level	0,1
RAID cache backup unit	No FBU support
Interface technology	SAS/SATA

Order code	Product Name	Height of bracket	Number of Connectors	Formfactor
S26361-F3842-E20	PSAS CP400i	Matching to system		Low profile
S26361-F3842-E2	PSAS CP400i	Matching to system	2	Low profile
S26361-F3842-L502	PSAS CP400i	Full Height / Low Profile	2	Low profile

Environment

Temperature (operating)	0 - 55 °C
Storage temperature	-45 - 105 °C

Compliance

Compliance notes	According to the corresponding system
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu with PSAS CP400i, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PSAS CP400i, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. <http://www.fujitsu.com/primergy>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>

©2016 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU LIMITED

Website: www.fujitsu.com
2017-02-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
©2016 Fujitsu Technology Solutions GmbH